

Holux S150

opening width - single panel	800 - 2.000 mm
opening width - double panel	1.000 - 3.000 mm
max leaf weight, single	150 kg
max leaf weight, double	2 x 150 kg
operator height	100 mm
operator depth	177 mm
opening speed	100 - 700 mm/s
closing speed	100 - 700 mm/s
hold-open time	0 - 30 s
ambient temperature	-15 to +50°C
protection class	IP20
100% german-made operator kit	✓
track profile	stainless steel
anti-noise rubber profile	✓
input power	230V AC ±10%, 50/60Hz
gear motor power	100 W
max power consumption	200 W
max operation cycles with 2.2 Ah backup battery (Optional)	450
possibility to adjust force limitation according to DIN18650 and EN16005	✓

Frame types:	
TBS	✓
THB	✓
UTS	✓
Saturn	✓
Frameless	✓

Holux S150

possibility to use safety sensors with testing signal for opening direction	✓
mechanical key switch (Optional)	✓
24V DC output for external accessories	✓
Power Lock	✓
possibility of using electromechanical lock (Optional)	✓
lock monitoring	✓
possibility of using digital programme switch (Optional)	✓
read-out error memory with error codes (with digital programme switch)	✓

Standards

DIN 18650	✓
EN 16005	✓
EN 60335	✓
EN ISO 13849-1:2008	✓
TÜV approved	✓
CE conformity	✓
tested for 1,000,000 cycles	✓